

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: BRENNFLECK, Matthias Michael

SERIAL NO.: 10/780,283

ART UNIT: 3679

FILED: February 17, 2004

EXAMINER: Kennedy J.T.

TITLE: CONNECTION ELEMENT

CERTIFICATE OF MAILING UNDER 37 CFR 1.8(a)

Commissioner for Patents
Portion. O. Box 1450
Alexandria, VA 22313-1450

Sir:

I hereby certify that the attached correspondence comprising:

AMENDMENT "B"

is being deposited with the United States Postal Service with sufficient postage as first class mail
in an envelope addressed to:

Commissioner for Patents
Portion. O. Box 1450
Alexandria, VA 22313-1450


on

4-3-06

Respectfully submitted,

Date

4-3-06



John S. Egbert
Reg. No. 30,627
Attorney for Applicant
Egbert Law Offices
412 Main Street, 7th Floor
Houston, Texas 77002
(713)224-8080



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: BRENNFLECK, Matthias Michael

SERIAL NO.: 10/780,283

ART UNIT: 3679

FILED: February 17, 2004

EXAMINER: Kennedy J.T.

TITLE: CONNECTION ELEMENT

Amendment B: CLAIM AMENDMENTS

Claims 1 - 18 (canceled herein). Claims 19 - 36 (canceled herein). Please cancel Claims 19 - 36 and substitute Claims 37 - 51 therefor as follows:

37. (new) A connection device for detachably connecting component parts comprising:

a connection element;

a first jaw sidewall extending from said connection element;

a second jaw sidewall extending from said connection element and arranged with respect to said first jaw sidewall so as to hold one of the component parts, said first and second jaw sidewalls being oriented in a first orientation with respect to said connection element;

a third jaw sidewall extending from said connection element;

a fourth jaw sidewall extending from said connection element and arranged with respect to said third jaw sidewall so as to hold another of the component parts, said third and fourth jaw sidewalls being oriented in a second orientation with respect to said connection element;

an adjusting means positioned in said connection element, at least one of said second and fourth jaw sidewalls adjustably mounted to said connection element, the at least one of said second and fourth jaw sidewalls having a first lateral leg that projects from one end thereof into